

HP0908 INTERNALLY LIT WINDCONE ASSEMBLY**Internally Lit Windcone**

FEC's Internally Lit Windcone meets the FAA AC 150/5324-27 (or latest revision) and ICAO Annex 14 design requirements. It is made of high strength, lightweight aluminum for durability in all environmental conditions. The hinged base on FEC's wind cone allows for easy accessibility when maintenance is needed. The base/ pole is powder coated orange for high visibility and long-lasting protection. Our wind cones can be installed on any surface. Optional mounting base available for structural connections.

Technical Details:

Operating voltage: 120/277 Vac

Maximum Power Consumption: 56 watts

Operating temperature: - 13F to 122F
- 25C to +50C

Operating LED Lifespan: Rated at 50,000 hours

Light Source:

Floodlights: (2)LED Par 38 Spotlight, COB, 25w, Clear

Obstruction Light: L-810 Red per
FAA Ac 150/5345-43

Physical Characteristics:**Dimensions:**

Height: 10' (3.048 m) from base to top
CUSTOM SIZES AVAILABLE

Base: (4) 3/4" (19.05mm) holes on a 7" (177.8mm) bolt circle

Shipping weight: 50lbs.





Replacement

Parts:

HP0192-18x6 (18" x 6') Replacement Windsock

HP0192-18x8 (18" x 8') Replacement Windsock

HP2080P Red LED Obstruction Light

HP0721 25 watt LED Par 38 Spotlight



HP0721 LED Par 38 Spotlight

Optional:

HP0333 Windcone Roof Mounting Base



HP0333 Mounting Base



HP0192 Replacement Windsock



FEC HELIPOINTS

WORLD HEADQUARTERS

5298 RIVER RD.

CINCINNATI, OH 45233

877-HELIPAD

