

WORLD HEADQUARTERS 5228 River Road Cincinnati, Ohio 45233

PHONE: 513-577-5150TOLL FREE: 1-877-HELIPAD

HP0908 AC INTERNALLY LIT WINDCONE ASSEMBLY

INTERNALLY LIT WINDCONE

FEC's Internally Lit Windcone meets the FAA AC 150/5324-27 (or latest revision) and ICAO Annex 14 design requirements. It is made of high strength, lightweight aluminum for durability in all environmental conditions. The hinged base on FEC's wind cone allows for easy accessibility when maintenance is needed. The base/ pole is powder coated orange for high visibility and long-lasting protection. Our wind cones can be installed on any surface. Optional mounting base available for structural connections.

| TECHNICAL DETAILS | |
|----------------------------|---|
| Operating Voltage: | 120/277 Vac |
| Maximum Power Consumption: | 56 watts |
| Operating Temperature: | -13F to 122F -25C to +50C |
| Operating LED Lifespan: | Rated at 50,000 hours |
| Light Source: | |
| Floodlights: | (2)LED Par 38 Spotlight, COB, 25w, Clear |
| Operating Voltage: | L-810 Red per FAA Ac 150/5345-43 |
| Operating Voltage: | |
| Operating Voltage: | |
| Operating Voltage: | 10' (3.048 m) from base to top CUSTOM SIZES AVAILABLE |
| Operating Voltage: | (4) 3/4" (19.05mm) holes on a 7" (177.8mm) bolt circle |
| Operating Voltage: | 50lbs. |





WORLD HEADQUARTERS 5228 River Road Cincinnati, Ohio 45233

PHONE: 513-577-5150TOLL FREE: 1-877-HELIPAD

HP0908 AC INTERNALLY LIT WINDCONE ASSEMBLY

| REPLACEMENT PARTS: | |
|------------------------|------------------------------|
| HP0192-18x6 (18" x 6') | Replacement Windsock |
| HP0192-18x8 (18" x 8') | Replacement Windsock |
| HP2080P | Red LED Obstruction Light |
| HP0721 | 25 watt LED Par 38 Spotlight |



HP0721 LED PAR 38 SPOTLIGHT

OPTIONAL REPLACEMENT PARTS:

HP0333

Windcone Roof Mounting Base



HP0333 MOUNTING BASE



HP0192 REPLACEMENT WINDSOCK



WORLD HEADQUARTERS 5228 River Road Cincinnati, Ohio 45233

PHONE: 513-577-5150TOLL FREE: 1-877-HELIPAD

HP0908 AC INTERNALLY LIT WINDCONE ASSEMBLY

