

DC POLE MOUNTED PERIMETER LIGHT 12/24 VDC OUTPUT FROM FEC CONTROLLER - NVG COMPATIBLE

HP1900 SERIES



DC INSET PERIMETER LIGHT
DISCONTINUED 1ST GENERATION

This newly redesigned Pole perimeter light is the latest addition to the FEC Heliports line of high quality LED lights.

Perimeter and Obstruction lights are one of the most important safety features on your heliport. They are used to mark and illuminate the FATO, TLOF, and Obstructions as well as to help the pilot locate the pad and safely land during night operations and inclement weather conditions.

KEY FEATURES:

- Mil-spec anodized cast aluminum body suitable for the harshest environments
- Pre-wired for quick and easy installations
- Standard color in Anodized Grey
- Anodized Blue, Red, and Gold finish are special order

TECHNICAL DETAILS

OPERATING VOLTAGE:

120/277V 50/60Hz input
12/24 VDC Output via FEC PLC
Controller

OPERATING POWER:

6 Watts @ 0.350ma

OPERATING TEMPERATURE:

- 40°F to 131°F
- 40°C to + 55°C

OPERATING LIFESPAN:

LED's Rated to 50,000 hrs

LIGHT SOURCE:

1x Osram Visible LED
3x Osram IR Diodes

STANDARD PART NUMBERS:

HP1971G True Green (528nm)
HP1972G Blue (470nm)
HP1973G White 6000K
HP1974G Yellow/Amber (590nm)
HP1982G Red

DC POLE MOUNTED PERIMETER LIGHT 12/24 VDC OUTPUT FROM FEC CONTROLLER - NVG COMPATIBLE

PHOTOMETRIC:

Standards
U.S. Department of Transportation, Federal Aviation Administration,
Memorandum, Heliport Perimeter Light for Visual Meteorological
Conditions, Engineering Brief No. 87

Parameter	Requirement	Measured	Result
Min. Peak Intensity	5 cd from 16° - 90°	12.6 cd	Pass
Min. Peak Intensity	10 cd from 0° - 15°	23.3 cd	Pass
Min. Avg Intensity	15 cd from 0° - 15°	46.7 cd	Pass

cd = Candela

Standards
International Civil Aviation Organization (ICAO):
Aerodromes, Annex 14, Volume 2, Fourth Edition, dated July 2013
Aerodromes, Annex 14, Volume 1, Seventh Edition, dated July 2016

Parameter	Requirement	Measured	Result
Min. Peak Intensity	3 cd from 21° - 90°	12.6 cd	Pass
Min. Peak Intensity	8 cd from 13° - 20°	36.1 cd	Pass
Min. Peak Intensity	15 cd from 11° - 13°	51.5 cd	Pass
Min. Peak Intensity	30 cd from 6° - 10°	41.7 cd	Pass
Min. Peak Intensity	15 cd from 2° - 5°	30.9 cd	Pass

Test Purpose - Performance Testing (Photometry and Chromaticity)

Test Dates - December 11, 2018

STANDARDS AND CERTIFICATIONS:

- FAA EB#87, L-860HR & HS
- FAA AC 150/5390-2 (Latest Rev.), Heliports Design Guide
- ICAO Annex 14, Volume II
- UK CAP 437
- UK CAP 1264

PHYSICAL CHARACTERISTICS:

Dimensions:

- Height 5 inches(127mm)
- Lid Diameter 6-1/2 inches(165.1mm)

Materials:

- Lens Tempered Glass
- Casting 356 T6 Aluminum Alloy

Mounting:

- 1"(25.4mm) NPT located on the bottom of each pole light

Materials:

- Casting 356 T6 Aluminum Alloy
- Light: 6lbs.

Notes: All machining on the Aluminum casting is done in house by FEC Heliports

PRODUCT DETAILS:

