

PAD-STAR® AC ELEVATED POLE MOUNT - 2ND GENERATION

HP2000 SERIES



AC INSET PERIMETER LIGHT
HP0270 Pole Optional. Pole not included.

This newly redesigned Pole perimeter light is the latest addition to the FEC Heliports line of high quality LED lights.

Perimeter and Obstruction lights are one of the most important safety features on your heliport. They are used to mark and illuminate the FATO, TLOF, and Obstructions as well as to help the pilot locate the pad and safely land during night operations and inclement weather conditions.

KEY FEATURES:

- Hermetically sealed optical assembly to mitigate condensation
- Infra-Red equipment standard on all PadStar Series lighting
- NVG Compatible
- 10-Year Limited Warranty
- Engineered and designed to be universally compatible with any existing heliport lighting system
- Mil-spec anodized cast aluminum body suitable for the harshest environments
- Pre-wired for quick and easy installations

TECHNICAL DETAILS

<p>OPERATING VOLTAGE: 100-240 VAC, 50/60Hz</p>	<p>OPERATING LIFESPAN: LED's Rated to 50,000 hrs</p>	<p>STANDARD PART NUMBERS: HP2060P True Green (528nm) HP2063P Blue (470nm) HP2061P White 6000K HP2062P Yellow/Amber (590nm) HP2080P Red</p>
<p>OPERATING POWER: 6 Watts @ 0.350ma</p>	<p>LIGHT SOURCE: 1x Osram Visible LED 3x Osram IR Diodes</p>	
<p>OPERATING TEMPERATURE: - 40°F to 131°F - 40°C to + 55°C</p>		

PAD-STAR® AC ELEVATED POLE MOUNT - 2ND GENERATION

PHOTOMETRIC:

Standards
U.S. Department of Transportation, Federal Aviation Administration,
Memorandum, Heliport Perimeter Light for Visual Meteorological
Conditions. Engineering Brief No. 87

Parameter	Requirement	Measured	Result
Min. Peak Intensity	5 cd from 16° - 90°	12.6 cd	Pass
Min. Peak Intensity	10 cd from 0° - 15°	23.3 cd	Pass
Min. Avg Intensity	15 cd from 0° - 15°	46.7 cd	Pass

cd = Candela

Standards
International Civil Aviation Organization (ICAO):
Aerodromes, Annex 14, Volume 2, Fourth Edition, dated July 2013
Aerodromes, Annex 14, Volume 1, Seventh Edition, dated July 2016

Parameter	Requirement	Measured	Result
Min. Peak Intensity	3 cd from 21° - 90°	12.6 cd	Pass
Min. Peak Intensity	8 cd from 13° - 20°	36.1 cd	Pass
Min. Peak Intensity	15 cd from 11° - 13°	51.5 cd	Pass
Min. Peak Intensity	30 cd from 6° - 10°	41.7 cd	Pass
Min. Peak Intensity	15 cd from 2° - 5°	30.9 cd	Pass

Test Purpose - Performance Testing (Photometry and Chromaticity)

Test Dates - December 11, 2018

STANDARDS AND CERTIFICATIONS:

- FAA EB#87, L-860HR & HS
- FAA AC 150/5390-2 (Latest Rev.), Heliports Design Guide
- ICAO Annex 14, Volume II
- UK CAP 437
- UK CAP 1264

PHYSICAL CHARACTERISTICS:

Dimensions:

- Height 5 inches(127mm)
- Lid Diameter 6-1/2 inches(165.1mm)

Materials:

- Lens Tempered Glass
- Casting 356 T6 Aluminum Alloy

Mounting:

- 1"(25.4mm) NPT located on the bottom of each pole light

Materials:

- Casting 356 T6 Aluminum Alloy
- Light: 6lbs.

Notes: All machining on the Aluminum casting is done in house by FEC Heliports

PRODUCT DETAILS:

